

**FRONTNICHE**

**12G - 6G - 3G**

*3<sup>rd</sup> Generation of Professional Blu-ray/DVD Player with 3G-SDI Output, Multi-Zone/Region with NEW IP O/P Option*

## *BLUE ROYCE III*

Introducing the 3<sup>rd</sup> Generation new Professional Blu-ray/DVD Player



“Blue Royce III” offers more features at half the cost of the original Mk I

- SDI + Embedded Audio O/P
- New Optional IP Output (Supports RTSP/RTP/RTMP/HTTP/UDP/ONVIF/HLS Unicast and Multicast protocols)
- Remote control by IR, RS-232C or IP
- Supports nearly all Blu-Ray, DVD, and audio CD formats
- Discrete 7.1 analogue surround sound outputs
- PAL/NTSC
- Front-loading USB slot for playback of image and audio files
- Coaxial digital (AES/EBU) and balanced XLR audio outputs
- Space saving 1RU chassis with removable ears
- Multi-Region
- Multi-Zone
- Panel lock and IR remote lock functions prevent unwanted or accidental operation
- Power-on Play button eliminates extra steps, and provides simplified, ultra-fast start up
- OSD (On Screen Display) hiding mode eliminates unwanted disc status updates
- Repeat mode offers an uninterrupted playback loop

Frontniche

**3G-SDI**

Frontniche  
Frontniche Stables  
Flawborough  
Nottingham  
NG13 9PA

Tel: + 44 (0)1572787814  
Fax: + 44 (0)709 2362114

Email: [sales@frontniche.com](mailto:sales@frontniche.com)

| Specification  |   |
|--|---|
| System   | Digital media player (Blu-ray Disc, DVD, CD, USB device [mass storage class]); AVCHD playback format  |
| Supported Disc Formats                                 | Blu-ray Disc<br>BD25, BD50, BD-ROM, BD-R, BD-RE<br>DVD<br>DVD, DVD+R, DVD-R, DVD+RW, DVD-RW, DVD-Audio (DVD-A)<br>CD<br>CD, CD-R, CD-RW, DTS Music Disc (DTS Audio CD, 5.1 Music Disc), HDCD, Super Video CD (SVCD), Video CD (VCD)   |
| Supported File Formats                                 | Video: .3gp, .avi, .dat, .dvix, .mkv, .mov, .mp4, .mpg, .m2ts, .ogm, .tp, .ts, .wmv, .zsf<br>Subtitles: .ass, .smi, .srt, .ssa, .sub<br>Audio<br>.ape, .flac, .m4a (AAC), .mp3, .wav<br>Picture<br>.gif, .jpg (or .jpeg), .png  |
| Supported File Systems                                 | FAT16, FAT32, NTFS<br>USB drive (mass storage class) with < 2 TB total capacity   |
| Video  | Resolutions<br>Auto, 480i/576i, 480p/576p, 720p, 1080i, 1080p<br>Aspect Ratios<br>16:9 Full, 16:9 Normal, 4:3 Pan & Scan, 4:3 Letterbox<br>System<br>NTSC, PAL,<br>IP O/P<br>RGB PC Level, RGB Video Level, YCbCr (4:4:4), YCbCr 4:2:2<br>Output<br>SDI + Embedded Audio<br>Decoding;<br>Video   DivX 3, 4, 5, 6; DivX HD; MPEG-1; MPEG-2; MPEG-4; MPEG-4 AVC (H.264);<br>VC-1 (Windows Media Video); Xvid<br>Audio   AAC; Dolby Digital; Dolby Digital Plus; Dolby TrueHD; DTS Digital Surround; DTS-HD; WMA |
| Audio  |   |
| Analogue Outputs                                       | Output Level (Balanced XLR)   +4dBu = +1.786 dBV<br>Output Level (Unbalanced RCA)   +6 dBV  |
| Digital Output   | Output Level (Coaxial)   0.5V, 75 Ω<br>Signal Format   AES/EBU  |
| Surround Audio   | DTS-Master Audio, DTS-HD High Resolution Audio, DTS Digital Surround, Dolby TrueHD, Dolby Digital (AC-3),<br>Dolby Digital Plus (7.1ch)   |
| Frequency Response                                     | 20 Hz – 20 kHz (+0.5 dB)  |
| Signal-to-Noise Ratio                                  | > 100 dB (A-weighted)   |
| Total Harmonic Distortion                              | < 0.05%   |
| Dynamic Range  | > 106 dB (A-weighted)   |
| Headroom   | 6dB   |
| Channel Separation                                     | > 90 dB   |
| Communication  |   |
| Remote Control   | Infrared protocol, > 200 mV transmission output level   |
| Serial Remote  | Connector: 9-pin D-Sub female, RS-232C<br>Mode: Full duplex<br>Baud Rate: 9600 or 38400 bps (selectable)  |
| Ethernet   | Connector: LAN port<br>Standards: Ethernet (10 Mbps), Fast Ethernet (100 Mbps)  |
| Other / General  |   |
| Connections  | (2) XLR audio outputs (L/R, balanced)<br>(2) RCA audio outputs (L/R, unbalanced)<br>(8) RCA audio outputs (7.1 surround sound)<br>(1) Coaxial digital audio/visual output<br>(1) BNC SDI audio/visual output<br>(1) LAN port (1) IP O/P<br>(1) 9-pin D-Sub female RS-232C port<br>(1) IEC power connection  |
| Power  | Connection: IEC<br>Requirement: 100–240 VAC, 50/60 Hz<br>Consumption: 20 W typical, < 0.5 W standby   |
| Environmental Conditions                               | Operating temperature: 41 – 95 °F (5 – 35 °C)<br>Operating humidity: 25 – 85%, no condensation  |
| Dimensions<br>(width x depth x height, with rack ears) | 19.00" x 10.75" x 1.73"<br>483 mm x 273 mm x 44 mm  |
| Weight<br>(with rack ears)                             | 5.9 lbs.<br>2.7 kg  |