

FRONTNICHE

12G - 6G - 3G

HD Passive Splitters



Overview:

- Splits a single signal into two outputs
- Supports *HD-SDI*, *SD-SDI* and *ASI* digital video formats
- Fault Tolerant (shorts or open circuit on any O/P has no effect on other O/P)
- Very high performance compared with competitor products
- Ultra compact units in standalone or 1RU rack mount versions

Application:

- Low cost 1 to 2 distribution amplifier. Multiple units to achieve
- 2, 4, 6, 8, 10, 12, 14, 16, 18, & 20 Channels.
- Signal split for dual-redundant signal processing architectures
- Simple monitoring split from main signal feed

Frontniche Ltd, Circuit Bureau Building, Unit 5 Factory Lane, Beeston, Nottingham, NG9 4AA.
Tel: +44 (0)1949851486 Fax: +44(0)709262114 EM:
sales@frontniche.com Web: www.frontniche.com

Specifications are subject to change without prior notice. E&OE.

HS275B Series Signal Splitters

Description:

The HS275B series of signal splitters conveniently split a single source into two signals for distribution with minimal loss. Since it is a passive device there is no requirement for power. These high performance devices are also fault tolerant, such that a cable fault or improper termination on one output does not affect the other.

As the units have a wideband capability, they can be used with all digital video signals as well as RF. When used with RF signals, they may also be used as a combiner.

The splitters are available in a compact single channel unit, or multiple channels in a 1RU rack unit. The rack unit is available in 6 and 12-channel variants with rear or front only connectors and in 10 and 20-channel versions with front to rear, or rear to front routing.

The HS275B range of splitters support all of the SMPTE digital video transmission rates and so are compatible with ASI, 3G-SDI, HD-SDI, and SD-SDI.

Specification:

Model	HS275B	-01S	-06F	-06R	-10A	-10B	-12F	-12R	-20A	-20B
Channels		1	6	6	10	10	12	12	20	20
Mode		1:2								
Orientation	inputs	N/A	Front	Rear	Front	Rear	Front	Rear	Front	Rear
	outputs	N/A	Front	Rear	Rear	Front	Front	Rear	Rear	Front
Impedance		75Ω ±2%								
Bandwidth		10MHz to 1.5GHz								
Compatibility		HD-SDI, SD-SDI, ASI, RF								
Return Loss		<20dB @ 270MHz to 1.5GHz;								
Insertion Loss		0.6dB typical								
Total Loss		3.7dB typical								
Amplitude Imbalance		0.25dB maximum								
Phase Imbalance		0.75degrees typical								
Output Isolation		28dB typical								
Channel Isolation		N/A	better than 85dB							
Size	height	20mm [0.85"]	1RU							
	width	50mm [2"]	19" rack mount							
	depth	30mm [1.2"]	30mm [1.2"]							
Weight		50g [1.7oz]	1.1kg [2.4lb]	1.2kg [2.6lb]	1.25kg [2.8lb]	1.4kg [3lb]				
Environmental		-25 to +55 deg C [32 to 131 deg F], 5%-95% non-condensing EN55103-1, EN55103, EN6095, FCC part 15								

Ordering Information:

WS275B-01S	1-Ch Passive Splitter, 3Gb/s, Standalone Unit
WS275B-06F	6-Ch Passive Splitter, 3Gb/s, 1RU Rack Unit, Front Connections
WS275B-06R	6-Ch Passive Splitter, 3Gb/s, 1RU Rack Unit, Rear Connections
WS275B-12F	12-Ch Passive Splitter, 3Gb/s, 1RU Rack Unit, Front Connections
WS275B-12R	12-Ch Passive Splitter, 3Gb/s, 1RU Rack Unit, Rear Connections
WS275B-10A	10-Ch Passive Splitter, 3Gb/s, 1RU Rack Unit, Front Inputs, Rear Outputs
WS275B-10B	10-Ch Passive Splitter, 3Gb/s, 1RU Rack Unit, Rear Inputs, Front Outputs
WS275B-20A	20-Ch Passive Splitter, 3Gb/s, 1RU Rack Unit, Front Inputs, Rear Outputs

Frontniche Ltd, Circuit Bureau Building, Unit 5 Factory Lane, Beeston, Nottingham, NG9 4AA.
 Tel: +44 (0)1949851486 Fax: +44(0)709262114 EM:
sales@frontniche.com Web: www.frontniche.com