

FRONTNICHE

12G - 6G - 3G

**Ultra Enigma 55" HDR UHD Monitor with 12G-SDI
Single & Quad Link I/P's**



FEATURES

- HDR (High Dynamic Range) display function with several ST2084 and HLG curves.
- Demo mode for HDR/SDR comparison.
- Lightillusion Calibration Software with Probe for 3D 'Look up Table' Generation.
- 2x BNC 12G-SDI with their respective loops for Single-Link UHD and 4K signals display.
- 4x BNC 3G-SDI for 4K and UHD signals display with Quad-Link.
- 4K 10 bit Quad image processing in "Square Division" and "2-Sample Interleave" formats.
- DCI 2.0 inputs (not compatible with HDCP) allowing for resolutions up to 2160p60.
- Monitor remote control through Ethernet port using IP protocol.
- Color space selection (3-D LUT) EBU, NTSC, SMPTE-C, REC709 and D-CINEMA.
- Color temperature selection: 3200K, 5500K, 6500K and 9300 K.
- Firmware upgrade via USB port. Remote control through GPI port (RJ45 connector).
- WaveForm and Vectorscope.
- Audio level meter for up to 16 channels.
- Peaking filter and False Colour.
- LTC and DVITC time-code display.
- Closed Caption according to 608 ANC, Transcoded 608 and CC708.
- Blue Only / Mono.
- Several marker formats with adjustable transparency and color: 4:3, 16:9, 14:9, 13:9, 2.35:1, and 1.85:1.
- Safe Area: 80%, 85%, 88%, 90%, 93%, 95%, EBU Graphic, Action.
- Center Marker with three selectable sizes.
- H/V Flip function.
- Aspect ratios: 4:3, 16:9, 15:9, 14:9, 13:9, 1.85:1, 2.35:1, 1:1, native.
- External power supply.
- 24" & 31" versions also available.

Frontniche Ltd, Circuit Bureau Building, Unit 5 Factory Lane, Beeston, Nottingham, NG9 4AA.

Tel: +44 (0)1949851486 Fax: +44(0)709262114

EM: sales@frontniche.com Web: www.frontniche.com

Specifications are subject to change without prior notice. E&OE.

FRONTNICHE

12G - 6G - 3G

Ultra Enigma 55" HDR UHD Monitor with 12G-SDI Single & Quad Link I/P's

Back Panel



- 4 SDI, input/output pairs with signal presence LED. They may operate as:
 - 2 x 12G-SDI switchable inputs, each one featuring its own follower output.
 - 4 x 3G-SDI inputs for 4K Quad-Link inputs, with its corresponding Quad-Link follower output.
- One DCI (Digital Components Input) connector supporting resolutions up to 2160p60.
- One RS 232C serial port.
- One RJ45 connector for GPI (general purpose input).
- One RJ45 connector for Ethernet control.
- A pair of RS 422 input and follower connectors for UMD/IMDI.
- One USB connector for Firmware upgrade



Front Control Panel

- Power switch
- 14 control and quick-access keys.
- Navigation encoder.
- Front tri-colour Tally .
- Headphone connector.
- 2 speakers.

Frontniche Ltd, Circuit Bureau Building, Unit 5 Factory Lane, Beeston, Nottingham, NG9 4AA.

Tel: +44 (0)1949851486 Fax: +44(0)709262114




EM: sales@frontniche.com Web: www.frontniche.com

Specifications are subject to change without prior notice. E&OE.

FRONTNICHE

12G - 6G - 3G

Ultra Enigma 55" HDR UHD Monitor with 12G-SDI Single & Quad Link I/P's

SPECIFICATIONS	FN4K 55
Active Area (Diagonal)	54.64" / 1387.8mm
MODES	
Video Modes	3840x2160(23.98/24/25/29.97/30/50/59.94/60p) 2048x1080p(23.98/24) 1920x1080p(50/60/30psf/25psf/24psf/30/25/24) 1920x1035i(60/59.94) 1920x1080i(50/59.94/60) 1280x720p(24/25/30/50/59.94/60) DCI  720p / 1080p / 2160p
INPUTS	
Digital Video Inputs(SDI)	12G / 3G HD SDI SMPTE ST 2082-10/SMPTE424&425/SMPTE 292M/296M. (It does not support dual link)
Digital Video Inputs DCI	Up to 2160p DCI  (Not Supported 4:2:0 Color Format /only 3840x2160_4096x2160 4:2:0 Color Format Supported)
PICTURE	
Aspect Ratios	Pantalla completa, 16:9, 4:3, 14:9, 13:9, 1.85:1, 2.85:1, Pixel a Pixel.
Pixel (RGB Trio) Arrangement	3840 H x 2160 V Pixels (8,294,400 Pixels, 16:9)
Pixel (RGB Trio) Pitch, Depth	0.315 mm x 0.315 mm 1.07 Billion de colors 10bit
Brightness, typical	500 cd/m2
Contrast Ratio	1100:1
Color Processor	10 bit color Processor
Viewing Angle, contrast>10:1	R/L 178(Typ.), U/D 178(Typ.)
Panel Response Time	8 ms (G to G)
CONTROLS	
User Controls	ST-BY, SDI1, SDI2, 2SI, QUAD, HDMI, F1 ~5, MENU, SEL/INPUT, UP, DOWN, ADJUST
Remote Controls	IR, TCP/IP, RS-422, RS-232
LIGHT	
Light Source (standard)	Light Emitting Diode Backlight system
LED Life	50,000 hrs (Min)
CONNECTORS	
SDI Video Connectors	BNC x 8: 2x HD-3G-12G Single-Link input / 2x output, 4x 12G Quad-Link / 4x output
DCI Connectors	1 x input, format 
DISPLAY	
Window (Display Area)	47.62 x 26.78" / 1209.6 x 680.4 mm
POWER, DIMENSIONS & MISCELLANEOUS	
DC Power	24 VDC ±10%,
DC Connector	XLR-5M (pin 1,2=Gnd, pin 4,5=+Volts)
AC Power (detached power supply included)	100-240 VAC, 50/60 Hz
AC Power Connector:	IEC 320-C14 3 pin Male
Cabinet Dimensions	1241.4 mm x 734.0mm x 79.0mm
Weight	25 Kg
Operating (full spec)	0 / +50°C, no condensation, 0 - 10,000 feet (3.048m)
Storage	- 20 / +60°C, no condensation, 0 - 40,000 feet (12.192m)

Frontniche Ltd, Circuit Bureau Building, Unit 5 Factory Lane, Beeston, Nottingham, NG9 4AA.

Tel: +44 (0)1949851486 Fax: +44(0)709262114

EM: sales@frontniche.com Web: www.frontniche.com

Specifications are subject to change without prior notice. E&OE.